

Safety data sheet according to UK REACH

Printing date 06.02.2025

Version number 5 (replaces version 4)

Revision: 06.02.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name Stain Mahogany

Article number: 11525-800171-000

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Paint

Coating

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

LOBA GmbH & Co. KG

Leonberger Straße 56 - 62

D-71254 Ditzingen

Tel.: +49 (0)7156/357-0

1.4 Emergency telephone number:

Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02

Signal word Danger

Hazard statements

H225 Highly flammable liquid and vapour.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P280 Wear protective gloves / eye protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH208 Contains Alkyl Amine Polymer w/Cr. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

(Contd. on page 2)

Safety data sheet according to UK REACH

Printing date 06.02.2025

Version number 5 (replaces version 4)

Revision: 06.02.2025

Product name Stain Mahogany

(Contd. of page 1)

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of the substances listed below with harmless additions.

· **Dangerous components:**

CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43-xxxx	ethanol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	25-50%
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-211-945-0011-60-xxxx	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	25-50%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43-xxxx	butanone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	<0.5%
CAS: 85029-57-8	Alkyl Amine Polymer w/Cr ⚠ Skin Sens. 1B, H317; Aquatic Chronic 3, H412	≥0.1-<0.5%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **After inhalation** Supply fresh air; consult doctor in case of symptoms.

· **After skin contact**

In general, the product is not irritating to the skin. Wash off the product with plenty of soap and water after skin contact.

· **After eye contact** Rinse opened eye for several minutes under running water.· **After swallowing** In case of persistent symptoms consult doctor.· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.· **4.3 Indication of any immediate medical attention and special treatment needed** Symptom Treat omanically.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· **Suitable extinguishing agents** CO₂, sand, extinguishing powder. Do not use water.· **For safety reasons unsuitable extinguishing agents**

Water.

Water with a full water jet.

· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

· 5.3 Advice for firefighters

· **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Prevent material from reaching sewage system, holes and cellars.

Inform respective authorities in case product reaches water or sewage system.

(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 06.02.2025

Version number 5 (replaces version 4)

Revision: 06.02.2025

Product name Stain Mahogany

(Contd. of page 2)

- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep containers tightly sealed.
Store in cool, dry conditions in well sealed containers.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** Store in cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed containers.
- **Storage class 3**
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

34590-94-8 Dipropylene glycol monomethyl ether

WEL Long-term value: 308 mg/m³, 50 ppm

Sk

78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppmLong-term value: 600 mg/m³, 200 ppm

Sk, BMGV

· Ingredients with biological limit values:

78-93-3 butanone

BMGV 70 µmol/L

Medium: urine

Sampling time: post shift

Parameter: butan-2-one

- **Additional information:** The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures** Wash hands during breaks and at the end of the work.
- **Breathing equipment:** Not required.

(Contd. on page 4)

Safety data sheet

according to UK REACH

Printing date 06.02.2025

Version number 5 (replaces version 4)

Revision: 06.02.2025

Product name Stain Mahogany

(Contd. of page 3)

· Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material: ≥ 0.4 mm**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

Value for the permeation: Level ≤ 6 **· Eye/face protection** Tightly sealed safety glasses.**SECTION 9: Physical and chemical properties****· 9.1 Information on basic physical and chemical properties****· General Information****· Physical state**

Liquid

· Colour:

According to product specification

· Smell:

Recognisable

· Odour threshold:

Not determined.

· Melting point/freezing point:

Not determined

· Boiling point or initial boiling point and boiling range

Not determined

· Flammability

Highly flammable.

· Lower:

Not determined.

· Upper:

Not determined.

· Flash point:

17 °C (DIN EN ISO 3679)

· Decomposition temperature:

Not determined.

· pH

Not determined.

· Viscosity:**· Kinematic viscosity at 20 °C**

13 s (DIN 53211/4)

· dynamic:

Not determined.

· Solubility**· Water:**

Not miscible or difficult to mix

· Partition coefficient n-octanol/water (log value)

Not determined.

· Steam pressure:

Not determined.

· Density and/or relative density**· Density at 20 °C**0.9 g/cm³ (Dichtekugel 10ml 20°C)**· Relative density**

Not determined.

· Vapour density

Not determined.

· Particle characteristics

not applicable, as liquid

· 9.2 Other information**· Appearance:****· Form:**

Fluid

· Important information on protection of health and environment, and on safety.**· Self-inflammability:**

Product is not selfigniting.

(Contd. on page 5)

GB

Safety data sheet according to UK REACH

Printing date 06.02.2025

Version number 5 (replaces version 4)

Revision: 06.02.2025

Product name Stain Mahogany

(Contd. of page 4)

· Explosive properties:	Product is not explosive. However, formation of explosive air/steam mixtures is possible.
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Highly flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

64-17-5 ethanol

Oral	LD50	7,060 mg/kg (rat)
Inhalative	LC50/4 h	20,000 mg/l (rat)

34590-94-8 Dipropylene glycol monomethyl ether

Oral	LD50	5,135 mg/kg (rat)
Dermal	LD50	9,500 mg/kg (rat)

78-93-3 butanone

Oral	LD50	3,300 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	12,000 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 06.02.2025

Version number 5 (replaces version 4)

Revision: 06.02.2025

Product name Stain Mahogany

(Contd. of page 5)

- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· Endocrine disrupting properties
--

78-93-3	butanone	List II
---------	----------	---------

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
 Water hazard class 1 (Self-assessment): slightly hazardous for water.
 Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
 After prior treatment product has to be landfilled or incinerated under adherence to the regulations pertaining to the disposal of especially hazardous waste.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|--|---|
| · 14.1 UN number or ID number
· ADR, IMDG, IATA | UN1263 |
| · 14.2 UN proper shipping name
· ADR
· IMDG, IATA | 1263 PAINT (vapour pressure at 50°C not more than 110 kPa)
PAINT |

(Contd. on page 7)

GB

Safety data sheet according to UK REACH

Printing date 06.02.2025

Version number 5 (replaces version 4)

Revision: 06.02.2025

Product name Stain Mahogany

(Contd. of page 6)

· 14.3 Transport hazard class(es)

· ADR, IMDG, IATA



· Class 3 Flammable liquids.
· Label 3

· 14.4 Packing group

· ADR, IMDG, IATA II

· 14.5 Environmental hazards:

· Marine pollutant: No

· 14.6 Special precautions for user

Warning: Flammable liquids.
· Kemler Number: 33
· EMS Number: F-E, S-E
· Stowage Category B

· 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 5L
· Excepted quantities (EQ) Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
· Transport category 2
· Tunnel restriction code D/E

· IMDG

· Limited quantities (LQ) 5L
· Excepted quantities (EQ) Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation":

UN 1263 PAINT (VAPOUR PRESSURE AT 50°C NOT MORE THAN 110 KPA), 3, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 06.02.2025

Version number 5 (replaces version 4)

Revision: 06.02.2025

Product name Stain Mahogany

(Contd. of page 7)

- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **National regulations**
- **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Alteration in the context will be marked with a cross (*).

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Abbreviations and acronyms:

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
- ICAO: International Civil Aviation Organisation
- ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Skin Sens. 1B: Skin sensitisation – Category 1B
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * Data compared to the previous version altered.