

Safety data sheet according to UK REACH

Printing date 07.10.2024

Version number 12 (replaces version 11)

Revision: 07.10.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name **2K Supra A.T. matt**

Article number: 11465-000003-000

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Dispersion paint/ Latex paint

Multi-pack product

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

LOBA GmbH & Co. KG

Leonberger Straße 56 - 62

D-71254 Ditzingen

United Kingdom:

Phi House

Southampton Science Park

Southampton, SO167NS

United Kingdom

Phone +442380766722

Tel.: +49 (0)7156/357-0

Informing department: service@loba.de

1.4 Emergency telephone number:

Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the GB CLP regulation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 Void

Hazard pictograms Void

Signal word Void

Hazard statements Void

Additional information:

EUH208 Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

EUH210 Safety data sheet available on request.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of the substances listed below with harmless additions.

Dangerous components:

CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-211-945-0011-60-xxxx	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	2.5-5%
CAS: 111-76-2 EINECS: 203-905-0 Index number: 603-014-00-0 Reg.nr.: 01-2119475108-36-xxxx	2-butoxyethanol Acute Tox. 3, H311; Acute Tox. 3, H331; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319 ATE: LD50 oral: 1,200 mg/kg LC50/4 h inhalative: 3 mg/l	<1.5%

(Contd. on page 2)

Safety data sheet

according to UK REACH

Printing date 07.10.2024

Version number 12 (replaces version 11)

Revision: 07.10.2024

Product name 2K Supra A.T. matt

(Contd. of page 1)

CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43-xxxx	butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	≤1%
CAS: 55965-84-9 EC number: 911-418-6 Index number: 613-167-00-5 Reg.nr.: 01-2120764691-48	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 Specific concentration limits: Skin Corr. 1C; H314: C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	≥0.00025-<0.0015%

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- After inhalation Supply fresh air; consult doctor in case of symptoms.
- After skin contact
In general, the product is not irritating to the skin. Wash off the product with plenty of soap and water after skin contact.
- After eye contact Rinse opened eye for several minutes under running water.
- After swallowing In case of persistent symptoms consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Symptom Treat omanically.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents Use fire fighting measures that suit the environment.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions:
Do not allow product to reach sewage system or water bodies.
Inform respective authorities in case product reaches water or sewage system.
- 6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- 6.4 Reference to other sections
No dangerous materials are released.
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.

(Contd. on page 3)

GB

Safety data sheet according to UK REACH

Printing date 07.10.2024

Version number 12 (replaces version 11)

Revision: 07.10.2024

Product name 2K Supra A.T. matt

See Section 13 for information on disposal.

(Contd. of page 2)

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** No special precautions necessary if used correctly.
- **Information about protection against explosions and fires:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Storage class 12**
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

34590-94-8 Dipropylene glycol monomethyl ether

WEL Long-term value: 308 mg/m³, 50 ppm
Sk

111-76-2 2-butoxyethanol

WEL Short-term value: 246 mg/m³, 50 ppm
Long-term value: 123 mg/m³, 25 ppm
Sk, BMGV

78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm
Long-term value: 600 mg/m³, 200 ppm
Sk, BMGV

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BMGV 240 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: butoxyacetic acid

78-93-3 butanone

BMGV 70 µmol/L
Medium: urine
Sampling time: post shift
Parameter: butan-2-one

· **Additional information:** The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures** Wash hands during breaks and at the end of the work.
- **Breathing equipment:** Not required.
- **Hand protection**
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 4)

Safety data sheet according to UK REACH

Printing date 07.10.2024

Version number 12 (replaces version 11)

Revision: 07.10.2024

Product name 2K Supra A.T. matt

(Contd. of page 3)

- **Material of gloves**

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material: ≥ 0.4 mm

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

Value for the permeation: Level ≤ 6

- **Eye/face protection** Safety glasses recommended during refilling.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Physical state**

Fluid

- **Colour:**

According to product specification

- **Smell:**

Recognisable

- **Odour threshold:**

Not determined.

- **Melting point/freezing point:**

Not determined

- **Boiling point or initial boiling point and boiling range**

100 °C

- **Flammability**

Not applicable.

- **Lower:**

Not determined.

- **Upper:**

Not determined.

- **Flash point:**

Not applicable

- **Decomposition temperature:**

Not determined.

- **pH**

Not determined.

- **Viscosity:**

- **Kinematic viscosity at 20 °C**

17 s (ISO 4 mm)

- **dynamic:**

Not determined.

- **Solubility**

- **Water:**

Not miscible or difficult to mix

- **Partition coefficient n-octanol/water (log value)**

Not determined.

- **Steam pressure:**

Not determined.

- **Density and/or relative density**

- **Density at 20 °C**

1.05 g/cm³ (Dichtekugel 10ml 20°C)

- **Relative density**

Not determined.

- **Vapour density**

Not determined.

- **Particle characteristics**

not applicable, as liquid

- **9.2 Other information**

- **Appearance:**

- **Form:**

Fluid

- **Important information on protection of health and environment, and on safety.**

- **Self-inflammability:**

Product is not selfigniting.

- **Explosive properties:**

Product is not explosive.

- **Change in condition**

- **Evaporation rate**

Not determined.

- **Information with regard to physical hazard classes**

- **Explosives**

Void

- **Flammable gases**

Void

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 07.10.2024

Version number 12 (replaces version 11)

Revision: 07.10.2024

Product name 2K Supra A.T. matt

(Contd. of page 4)

· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

34590-94-8 Dipropylene glycol monomethyl ether

Oral	LD50	5,135 mg/kg (rat)
Dermal	LD50	9,500 mg/kg (rat)

111-76-2 2-butoxyethanol

Oral	LD50	1,200 mg/kg (ATE) 1,480 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (guinea pig)
Inhalative	LC50/4 h	3 mg/l (ATE) 450 mg/l (rat)
	NOAEC	>125 mg/m ³ (ra)

78-93-3 butanone

Oral	LD50	3,300 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	12,000 mg/l (rat)

55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Oral	LD50	457 mg/kg (rat)
	ATE	64 mg/kg (rec)

(Contd. on page 6)

GB

Safety data sheet according to UK REACH

Printing date 07.10.2024

Version number 12 (replaces version 11)

Revision: 07.10.2024

Product name 2K Supra A.T. matt

(Contd. of page 5)

Dermal	LD50	660 mg/kg (rat)
	ATE	87 mg/kg (rec)
Inhalative	LC50/4 h	0.33 mg/l (rat)
	ATE	0.17 mg/l (rec)
	LC50/96 h	0.188 mg/L (fish)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

78-93-3 butanone

List II

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

EC50/48 h	0.1 mg/L (daphnia)
EC50/72 h	0.027 mg/L (Algae)
NOEC	0.0012 mg/L (Algae)
	0.004 mg/L (daphnia)
	0.098 mg/L (fish)

- **12.2 Persistence and degradability**

55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

OECD 301 D Closed Bottle Test	>60 % (not specified)
-------------------------------	-----------------------

- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

GB

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 07.10.2024

Version number 12 (replaces version 11)

Revision: 07.10.2024

Product name 2K Supra A.T. matt

(Contd. of page 6)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
After prior treatment product has to be landfilled or incinerated under adherence to the regulations pertaining to the disposal of especially hazardous waste.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, ADN, IMDG, IATA Void

· 14.2 UN proper shipping name

· ADR, ADN, IMDG, IATA Void

· 14.3 Transport hazard class(es)

· ADR, ADN, IMDG, IATA

· Class Void

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

· 14.6 Special precautions for user

Not applicable.

· 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

· UN "Model Regulation":

Void

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

67-64-1 acetone

Listed

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· National regulations

· Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

GB

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 07.10.2024

Version number 12 (replaces version 11)

Revision: 07.10.2024

Product name 2K Supra A.T. matt

(Contd. of page 7)

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Alteration in the context will be marked with a cross (*).

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Relevant phrases

H225 Highly flammable liquid and vapour.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H310 Fatal in contact with skin.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H331 Toxic if inhaled.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.
EUH071 Corrosive to the respiratory tract.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Department issuing data specification sheet: Product safety

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Flam. Liq. 2: Flammable liquids – Category 2
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 2: Acute toxicity – Category 2
Acute Tox. 3: Acute toxicity – Category 3
Skin Corr. 1C: Skin corrosion/irritation – Category 1C
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1A: Skin sensitisation – Category 1A
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

· * Data compared to the previous version altered.